



1200 Gehl Drive, Yankton, SD 57078
 Phone: 1-605-665-8415 Fax: 1-605-665-0810
 www.DakotaTrailer.com

48' Aluminum Trailer



Triple or 10'2" Spread Axle
 Double Hopper
 Bushel Capacity: Level-1168; Heaped-1353
 Dimensions: 67" or 72" side Height; 102" Width

STANDARD SPECIFICATIONS

Undercoating; 22,500 lb. Capacity axle with outboard mounted hubs and drums; Anti-Lock Brakes with Automatic Slack Adjusters; Two speed 50,000 lb Landing Legs; I.C.C. standard sealed beam type Lighting; I.C.C. Reflective tape, Mud Flaps, Ladder and Catwalk (front & rear); 67" Height & 96" or 102" Width. All Trailers also come equipped with Shur-Lok roll Tarp.

Tire Options (Hub Piloted Rims)

11R 24.5 New Radials on Steel Rims
 11R 22.5 New Radials on Steel Rims
 24.5 Low Pro First Time Caps on Steel Rims
 Aluminum Rims

Shur-Lok Tarp Standard Features

Double Ridge Straps
 Front Shur Return
 Easy Off Tarp Stops

AXLE	LENGTH	WIDTH	HEIGHT	LEVEL		HEAPED	
				CU. FT.	BUSHEL	CU. FT.	BUSHEL
TANDEM/SPREAD	48'	102'	67"	1459	1168	1555	1244
TANDEM/SPREAD	48'	102"	72"	1595	1276	1691	1353

